

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Round Metallic Beads ( Ball-Bearing type of appearance) Mixture

**Product Name:** Multiple - Casting Alloys, Gold & Silver Grains, Solders, Wrought Products & Pure Metals

**Other Means of Identification:** Yellow / White / Green / Pink / Brown Gold Master Alloys & Grains. Brass & Bronze alloys. Sterling Silver Master alloys & grains. Solder Master Alloys & Solders. Platinum & Palladium Grains & Master Alloys. All Wires / Sheets / Tubing & other wrought products.

### Intended Use of the Product

For melting & fabrication for the sole purpose of jewelry manufacturing only.

### Name, Address, and Telephone of the Responsible Party

#### Company

United Precious Metal Refining, Inc.

2781 Townline Road

Alden, NY 14004

TEL: (716) 683-8334 (800) 999-FINE

FAX: (716) 683-5433 (800) 533-6657

### Emergency Telephone Number

**Emergency Number** : 1-716-683-8334

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Metal Alloys :

### Classification (GHS-US)

Skin Sens. 1 H317

Carc. 2 H351

STOT RE 1 H372

### Label Elements

#### GHS-US Labeling

**Hazard Pictograms (GHS-US)** :



**Signal Word (GHS-US)** :

Danger

**Hazard Statements (GHS-US)** :

H317 – May cause an allergic skin reaction.  
 H351 – Suspected of causing cancer.  
 H372 – Causes damage to organs through prolonged or repeated exposure.

**Precautionary Statements (GHS-US)** :

P201 – Obtain special instructions before use.  
 P202 – Do not handle until all safety precautions have been read and understood.  
 P260 – Do not breathe dust, fume.  
 P264 – Wash hands, forearms and face thoroughly after handling.  
 P270 – Do not eat, drink or smoke when using this product.  
 P272 – Contaminated work clothing must not be allowed out of the workplace.  
 P280 – Wear protective gloves, protective clothing, face protection, eye protection.  
 P302+P352 – IF ON SKIN: Wash with plenty of water.  
 P308+P313 – If exposed or concerned: Get medical advice/attention.  
 P314 – Get medical advice/attention if you feel unwell.  
 P321 – Specific treatment (see Section 4).  
 P333+P313 – If skin irritation or rash occurs: Get medical advice/attention.  
 P362+P364 – Take off contaminated clothing and wash it before reuse.  
 P405 – Store locked up.  
 P501 – Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Other Hazards

Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath. If heated to the point of fume generation, zinc fumes may cause metal fume fever. Otherwise, zinc is non-toxic.

This product is present in a massive form as an alloy. It does not present the same hazards when the individual components are in their powdered forms. The materials present in this product in their powdered forms present aquatic toxicity to the environment and carcinogenicity. When processed or where dust is generated a combustible dust hazard may be present. Avoid generating dust, generating sparks, ignition sources, and take all precautions.

Under normal use and handling of the solid form of this material there are few health hazards. Cutting, welding, melting, grinding etc. of these materials will produce dust, fume or particulate containing the component elements of these materials. Exposure to the dust, fume or particulate of these materials may present significant health hazards. Exposure to dust or fume may cause irritation of the eyes, skin and respiratory tract. Fine particulates dispersed in air may present an explosion hazard.

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Silver	(CAS No) 7440-22-4	< 0.1, 0.1 – 1, 1 – 5, 5 – 10, 10 – 30, 30 – 60, 60 – 95	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Copper	(CAS No) 7440-50-8	5 – 10, 10 – 30, 30 – 60, 60 -90	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Nickel	(CAS No) 7440-02-0	< 0.1, 0.1 – 1, 1 – 5, 5 – 10, 10 – 30	Skin Sens. 1, H317 Carc. 2, H351 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Zinc	(CAS No) 7440-66-6	1 – 5, 5 – 10, 10 – 30	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Tin	(CAS No) 7440-31-5	< 0.1, 0.1 – 1, 1 – 5	Comb. Dust
Platinum	(CAS No) 7440-06-4	< 0.1, 0.1 – 1, 1 – 5, 5 – 10, 10 – 30, 30 – 60, 60 – 95	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Gold	(CAS No) 7440-57-5	< 0.1, 0.1 – 1, 1 – 5, 5 – 10, 10 – 30, 30 – 60, 60 – 95	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Palladium	(CAS No) 7440-05-3	< 0.1, 0.1 – 1, 1 – 5, 5 – 10, 10 – 30, 30 – 60, 60 – 95	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Ruthenium	(CAS No) 7440-18-8	< 0.1,	Comb. Dust

# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

		0.1 – 1, 1 – 5	Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Iridium	(CAS No) 7439-88-5	< 0.1, 0.1 – 1, 1 – 5	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Cobalt	(CAS No) 7440-48-4	< 0.1, 0.1 – 1, 1 – 5	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Rhenium	(CAS No) 7440-15-5	< 0.1, 0.1 – 1	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Indium	(CAS No) 7440-74-6	< 0.1, 0.1 – 1, 1 – 5, 5 – 10,	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Gallium	(CAS No) 7440-55-3	< 0.1, 0.2 – 1, 1 – 5, 5 – 10,	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Germanium	(CAS No) 7440-56-4	< 0.1, 1.1 – 1, 1 – 5,	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Silicon	(CAS No) 7440-21-3	< 0.1, 1.2 – 1, 1 – 5, 5 – 10,	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Boron	(CAS No) 7440-42-8	< 0.1, 1.3 – 1, 1 – 5,	Comb. Dust Aquatic Acute 1, H400 Aquatic Chronic 3, H412

Full text of H-phrases: see section 16

More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary due to varying composition.

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** IF exposed or concerned: Get medical advice/attention. Never give anything by mouth to an unconscious person.

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Keep at rest and in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash with plenty of soap and water. Wash contaminated clothing before reuse. Obtain medical attention if irritation persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Obtain medical attention if irritation persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting.

# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### **Most Important Symptoms and Effects Both Acute and Delayed**

**General:** May cause an allergic skin reaction. Welding, cutting, or processing this material may release dust or fumes that are hazardous.

**Inhalation:** Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

**Skin Contact:** May cause an allergic skin reaction. Dust from physical alteration of this product causes skin irritation.

**Eye Contact:** Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** In massive form, no hazard exists. If physically altered to present slivers, ribbons, dusts or fumes from molten material: Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If exposed or concerned, get medical advice and attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

### **Extinguishing Media**

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire. Do not use water when molten material is involved, may react violently or explosively on contact with water.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** A non-combustible material, not considered flammable but will melt at 1616 °F.

**Explosion Hazard:** In molten state: reacts violently with water (moisture).

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Under fire conditions, hazardous fumes will be present. In case of dust production:

**Firefighting Instructions:** Exercise caution when fighting any chemical fire.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Oxides of zinc. Oxides of tin. Oxides of nickel. Oxides of copper. Oxides of silver.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Avoid all eye and skin contact and do not breathe vapor and mist.

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area.

### **Environmental Precautions**

Prevent entry to sewers and public waters.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Contain and collect as any solid.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. For particulates and dust: Avoid actions that cause dust to become airborne during clean-up such as dry sweeping or using compressed air. Use HEPA vacuum or thoroughly wet with water to clean-up dust. Use PPE described in Section 8.

### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 7: HANDLING AND STORAGE

#### Precautions for Safe Handling

**Additional Hazards When Processed:** May generate flammable/explosive dusts or turnings when brushed, machined or ground. Use care during processing to minimize generation of dust. Where excessive dust may result, use approved respiratory protection equipment. Heating of product can release toxic or irritating fumes; ensure proper ventilation is employed, proper precautions are enforced, and applicable regulations are followed. Inhalation of fumes may cause metal fume fever.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

#### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place.

**Specific End Use(s)** For melting only.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Silver (7440-22-4)		
Mexico	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (dust and fume)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.01 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.01 mg/m <sup>3</sup> (dust)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (dust)
Alberta	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
British Columbia	OEL STEL (mg/m <sup>3</sup> )	0.03 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m <sup>3</sup> )	0.01 mg/m <sup>3</sup>
Manitoba	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (dust and fume)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (dust and fume)
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (dust and fume)
Nunavut	OEL STEL (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (dust and fume)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (dust and fume)
Québec	VEMP (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	0.03 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	0.01 mg/m <sup>3</sup>

Nickel (7440-02-0)		
Mexico	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (inhalable fraction)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.015 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
Manitoba	OEL TWA (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (inhalable fraction)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>

# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (inhalable fraction)
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (inhalable fraction)
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (inhalable)
<b>Prince Edward Island</b>	OEL TWA (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (inhalable fraction)
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
<b>Saskatchewan</b>	OEL STEL (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> (inhalable fraction)
<b>Saskatchewan</b>	OEL TWA (mg/m <sup>3</sup> )	1.5 mg/m <sup>3</sup> (inhalable fraction)
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
<b>Tin (7440-31-5)</b>		
<b>Mexico</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Mexico</b>	OEL STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup>
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Ontario</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Prince Edward Island</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Saskatchewan</b>	OEL STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup>
<b>Saskatchewan</b>	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Copper (7440-50-8)</b>		
<b>Mexico</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>Mexico</b>	OEL STEL (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (fume) 2 mg/m <sup>3</sup> (dust and mist)
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (dust and mist) 0.1 mg/m <sup>3</sup> (fume)
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (dust, fume and mist)
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (dust and mist)
<b>Manitoba</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>Newfoundland &amp; Labrador</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>Nova Scotia</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	0.6 mg/m <sup>3</sup> (fume)
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	0.6 mg/m <sup>3</sup> (fume)
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)

# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Ontario	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
Québec	VEMP (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	0.6 mg/m <sup>3</sup> (fume)
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
Yukon	OEL STEL (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)
Yukon	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (fume)

### Exposure Controls

**Appropriate Engineering Controls:** Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Protective clothing. Gloves. Safety glasses. Dust formation: dust mask.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Wear suitable protective clothing. Wash contaminated clothing before reuse.

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Metallic
Odor	: Odorless
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: 85.0 °F – 3215.0 °F Nominal
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 6.30 - 12.00
Solubility	: Not available
Partition Coefficient: N-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Hazardous reactions will not occur under normal conditions.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Avoid creating or spreading dust.

**Incompatible Materials:** When molten: water.

**Hazardous Decomposition Products:** Inhalation of fumes may cause metal fume fever.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

**Serious Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not classified

**Carcinogenicity:** Suspected of causing cancer. Not classified.

**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs through prolonged or repeated exposure. Not classified.

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Dust from physical alteration of this product causes skin irritation.

**Symptoms/Injuries After Eye Contact:** Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** In massive form, no hazard exists. If physically altered to present slivers, ribbons, dusts or fumes from molten material: Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

#### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

<b>Silver (7440-22-4)</b>	
LD50 Oral Rat	> 2000 mg/kg
<b>Nickel (7440-02-0)</b>	
LD50 Oral Rat	> 9000 mg/kg
<b>Tin (7440-31-5)</b>	
LD50 Oral Rat	700 mg/kg
<b>Nickel (7440-02-0)</b>	
IARC Group	2B
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.

### SECTION 12: ECOLOGICAL INFORMATION

**Toxicity** No additional information available

<b>Zinc (7440-66-6)</b>	
LC50 Fish 1	2.16 - 3.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.139 - 0.908 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	0.211 - 0.269 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])



# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Silver (7440-22-4)</b>	
LC50 Fish 1	0.00155 - 0.00293 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	0.00024 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	0.0062 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
NOEC chronic fish	390 ng/l (Exposure time: 28d - Species: Pimephales promelas)
<b>Nickel (7440-02-0)</b>	
LC50 Fish 1	100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
EC50 Daphnia 1	13 (13 - 200) µg/l (Exposure time: 48h - Species: Ceriodaphnia dubia [static])
LC 50 Fish 2	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 2	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 2	0.174 (0.174 - 0.311) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])
<b>Copper (7440-50-8)</b>	
LC50 Fish 1	<= 0.0068 (0.0068 - 0.0156) mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 1	0.0426 (0.0426 - 0.0535) mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
LC 50 Fish 2	0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	0.031 (0.031 - 0.054) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])

### Persistence and Degradability

<b>Casting Alloys &amp; Pure Metals</b>	
Persistence and Degradability	Not established.
<b>Copper (7440-50-8)</b>	
Persistence and Degradability	Not readily biodegradable.

### Bioaccumulative Potential

<b>Casting Alloys &amp; Pure Metals</b>	
Bioaccumulative Potential	Not established.

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Treatment Methods:** Recycle product or dispose properly.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, and international regulations.

## SECTION 14: TRANSPORT INFORMATION

<b><u>In Accordance with DOT</u></b>	Not regulated for transport
<b><u>In Accordance with IMDG</u></b>	Not regulated for transport
<b><u>In Accordance with IATA</u></b>	Not regulated for transport
<b><u>In Accordance with TDG</u></b>	Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

<b>Casting Alloys &amp; Pure Metals</b>	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
<b>Zinc (7440-66-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 % (dust or fume only)

# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Silver (7440-22-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>RQ (Reportable Quantity, Section 304 of EPA's List of Lists):</b>	1000 lb < 100 um CERCLA/SARA RQ CHANGE TITLE
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Nickel (7440-02-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>RQ (Reportable Quantity, Section 304 of EPA's List of Lists):</b>	100 lb (only applicable if particles are < 100 µm)
<b>SARA Section 313 - Emission Reporting</b>	0.1 %
<b>Tin (7440-31-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Copper (7440-50-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>SARA Section 313 - Emission Reporting</b>	1.0 %

### US State Regulations

<b>Nickel (7440-02-0)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Zinc (7440-66-6)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Silver (7440-22-4)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Nickel (7440-02-0)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Tin (7440-31-5)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Copper (7440-50-8)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	

### Canadian Regulations

<b>Casting Alloys &amp; Pure Metals</b>	
<b>WHMIS Classification</b>	Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

# Casting Alloys, Solders, Wrought products & Pure Metals

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations



### Zinc (7440-66-6)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification      Uncontrolled product according to WHMIS classification criteria

### Silver (7440-22-4)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification      Uncontrolled product according to WHMIS classification criteria

### Nickel (7440-02-0)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 0.1 %

WHMIS Classification      Class D Division 2 Subdivision B - Toxic material causing other toxic effects

### Tin (7440-31-5)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification      Uncontrolled product according to WHMIS classification criteria

### Copper (7440-50-8)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification      Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 10/31/2014

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
	May form combustible dust concentrations in air
H317	May cause an allergic skin reaction
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

# Casting Alloys, Solders, Wrought products & Pure Metals

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

---

## **Party Responsible for the Preparation of This Document**

United Precious Metal Refining, Inc.

2781 Townline Road

Alden, NY 14004

T: (716) 683-8334

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS 2